

www.vidiwavefueltechnology.co.uk +44 (0) 1908 690090 Vidiwave Fuel Technology Limited Unit 5, Beaufort Court, Roebuck Way, Knowlhill, Milton Keynes. MK5 8HL

Product Datasheet

Part Code: 10-200-001-00

IP66 WIMS Client Module - Rail

Wireless Intelligent Monitoring System

WIMS is a wireless integrated management solution comprising of an integrated VPN solution using 3G and 5GHz wireless LAN combined with an advanced embedded router, data logging, FTP server, email server and PUSH diagnostics. At its core, is a hybrid embedded linux OS platform, with proven reliability and long term stability. Which provides clients with a remote diagnostics and monitoring platform and the ability to create custom upgrades for future hardware integrations.

Key Features

- IP66 Rated Enclosure
- IP66 M12 Connectors
- Zero Config
- Ultra Secure P2P VPN Technology protects 3G / CDMA
 / WLAN and LAN to (AES-256) Mil-Spec standards
- Built on Embeded Linux OS for robustness and reliability
- 4GB Solid state compact flash memory
- Remote Health Checking of Depot WLAN System via GPRS / 3G and ADSL
- Supports fixed IP multi ports addressing via DHCP sim cards
- PUSH Diagnostics / Alerts and Exception Reporting direct to your Maintenance Provider
- Embedded Linux Remote Agent syncs information to a Headend Server to give instant Fault Visability and Reporting via 3G and WLAN
- Supports Full Video Management including Playback / Preview and Backup via GPRS / 3G and WLAN
- Integrated Video Backup to a Secure Web-Based Video Vault with Video Sharing Feature for Secure CCTV Evidence Distribution



Specifications

| Additional Features | Simple access to WIMS set up / management interface via Secure Web-Portal using any Browser |
|----------------------------------|---|
| | Supports Health Checking to other Legacy CCTV Systems** |
| | Supports Wake-on-LAN |
| | Supports all cellular technologies |
| | Supports both 2.4 and 5 GHz WLAN networks |
| | Full Mesh Networking acts as a repeater / mesh / booster in a multi device network |
| Physical Dimensions: (W x H x D) | 230mm x 230mm x 50mm |
| | |



www.vidiwavefueltechnology.co.uk +44 (0) 1908 690090 Vidiwave Fuel Technology Limited Unit 5, Beaufort Court, Roebuck Way, Knowlhill, Milton Keynes. MK5 8HL

Product Datasheet

WIMS Client Module - Rail

Specifications.....continued

| Wireless Modules | Enterprise Class Wireless LAN - via Mini PCI | 802.11a/b/g (up to 108Mbs) - Supports all 2.4 & 5GH WLAN | |
|-----------------------------------|---|---|--|
| | | Up to 4 Watts Transmit Power - External Range up to +500m (5 GHz) | |
| | | Advanced WLAN Security - WEP WPA AES, WPA2 (IEE 802.11i), (IEEE 802.1x Authentication) | |
| | | Additional support for 802.11 d, h, i, j including Mul- ti-Country Roaming | |
| | | DFS/TPC: Dynamic Frequency Selection/Transmit Power Control for 5 GHZ Mobile Fleet Operation in Ground Radar Area like Airports | |
| | | Support for 802.11e, the QOS Standard for Wireless Multimedia Enhancements | |
| | Mobile - via Mini PCI | Support for Third Generation (3G) - Digital Cellular Standards Compliant | |
| | | Global Support for Quad-Band EDGE / GPRS / GSM / CDMA - 850/900/1800/1900 Mhz | |
| | | Supports Tri-Band UMTP / 4G / LTE | |
| | | Peak Download Speed up to 7.2 Mbps* | |
| | | Peak Upload Speed up to 2.0 Mbps* | |
| | | Supports Dual Antenna Diversity for Improved Performance | |
| Data / Failure Monitoring Options | TCP/IP Network Serial Bus, WLAN 5 GHz HDD, WLAN 2.4 GHz Processor Health, USB devices, Remote, Work- stations, Managed HUB / ADSL routers - Via push diagnostics engine to cloud based condition monitoring and alerting server - (VidimonIQ) | | |
| Main PCB Specification | Operating System Custom Embedded Linux | | |
| | CPU 500Mhz AMD Geode LX800 DRAM 256Mb DDR DRAM | | |
| | Storage 4Gb SLC Compact Flash OS and Samba | | |
| | Power DC Jack or Passive POE, 7VDC to 20VDC | | |
| | Connectivity 2 Ethernet Channels (via VT6105M 10/ 100) | | |
| | I/O DB9 Serial Port, Dual USB port | | |
| | Supports POE via Vidiwave bespoke Injector | Supports POE via Vidiwave bespoke Injector | |
| Built-in VPN Technology | AES-256 (Advanced Encryption Standard) compl | AES-256 (Advanced Encryption Standard) compliant on all comminucations. (Cellular, LAN, WAN, WLAN) | |
| | AES-256 runs 14 simultaneous cycles for 256-Bit keys, delivering the highest standard of network data encryption currently available | | |
| | AES-256 is the encryption standard adopted by the US government | | |
| | AES-256 fully complies with the ISO/IEC 18033-3 | standard | |
| | AES-256 is used by NSA and other sucurity agen | cies worldwide with "Top Secret" encryption requirements | |
| | Peer-to-peer direct connection technology for increased speed and security | | |
| | VPN Supports RDP / VNC / Telnet / SSH / FTP / SF | TP and WOL over 3G + WLAN | |
| | * Network provider dependant | | |
| | | Page 2 | |